



Section 1 - Identification Of Chemical Product And Company

GE Silicones Australia Pty Ltd
175 Hammond Rd
Dandenong Vic 3175
AUSTRALIA

Phone 1800 034 427 (business hours)
Fax: + 61 3-9794 8563

Substance: Organotin compound.
Trade Name: RTV 577
Product Use: Catalyst.
Creation Date: November, 2006
Revision Date: October, 2006

Section 2 - Hazards Identification

Statement of Hazardous Nature

This product is classified as: Hazardous according to the criteria of NOHSC Australia.
Dangerous according to the Australian Dangerous Goods (ADG) Code.

Risk Phrases: R48/22, R36/38, R50/53. Harmful: danger of serious damage to health by prolonged exposure if swallowed. Irritating to eyes and skin. Very toxic to aquatic organisms, may cause long-term adverse effects to the aquatic environment.

Safety Phrases: S20, S26, S61, S24/25, S36/37/39. When using, do not eat or drink. In case of contact with eyes, rinse immediately with plenty of water and contact a doctor or Poisons Information Centre. Avoid release to the environment. Refer to special instructions/Safety Data Sheets. Avoid contact with skin and eyes. Wear suitable protective clothing, gloves and eye/face protection.

SUSDP Classification: S7

ADG Classification: Class 9 (ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.)

UN Number: 3082

Emergency Overview

Physical Description & colour: Colourless liquid.

Odour: Mild odour.

Major Health Hazards: may cause serious damage to health by prolonged exposure, irritating to eyes and skin, harmful if swallowed.

Potential Health Effects

Inhalation

Short term exposure: Significant inhalation exposure is considered to be unlikely. In addition product is unlikely to cause any discomfort or irritation, but inhalation of small quantities may, over time, cause serious health problems.

Long Term exposure: No data for health effects associated with long term inhalation.

Skin Contact:

Short term exposure: No data re harmful effects. Treat as harmful by skin absorption. However product is a skin irritant. Symptoms may include itchiness and reddening of contacted skin. Other symptoms may also become evident, but all should disappear once exposure has ceased.

Long Term exposure: No data for health effects associated with long term skin exposure.

Eye Contact:

Short term exposure: Exposure via eyes is considered to be unlikely. This product is an eye irritant. Symptoms may include stinging and reddening of eyes and watering which may become copious. Other symptoms may also become evident. If exposure is brief, symptoms should disappear once exposure has ceased. However, lengthy exposure or delayed treatment may cause permanent damage.

Long Term exposure: No data for health effects associated with long term eye exposure.

Ingestion:

Short term exposure: Significant oral exposure is considered to be unlikely. Available data shows that this product is harmful, but symptoms are not available.

Long Term exposure: danger of serious damage to health by prolonged exposure if swallowed.



Material Safety Data Sheet

Carcinogen Status:

NOHSC: No significant ingredient is classified as carcinogenic by NOHSC.

NTP: No significant ingredient is classified as carcinogenic by NTP.

IARC: No significant ingredient is classified as carcinogenic by IARC.

Section 3 - Composition/Information on Ingredients

Ingredients	CAS No	Conc,%	TWA (mg/m ³)	STEL (mg/m ³)
Dibutyl tin dilaurate	77-58-7	>99	0.1	0.2

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non hazardous ingredients are also possible.

The TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The STEL (Short Term Exposure Limit) is an exposure value that should not be exceeded for more than 15 minutes and should not be repeated for more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak" is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

Section 4 - First Aid Measures

General Information:

You should call The Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 1126 from anywhere in Australia (0800 764 766 in New Zealand) and is available at all times. Have this MSDS with you when you call.

Inhalation: First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Skin Contact: Quickly and gently blot away excess liquid. Wash gently and thoroughly with warm water (use non-abrasive soap if necessary) for 10-20 minutes or until product is removed. Under running water, remove contaminated clothing, shoes and leather goods (e.g. watchbands and belts) and completely decontaminate them before reuse or discard. If irritation persists, repeat flushing and seek medical attention.

Eye Contact: Quickly and gently blot material from eyes. Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for 20 minutes or until the product is removed, while holding the eyelid(s) open. Take care not to rinse contaminated water into the unaffected eye or onto the face. Obtain medical attention immediately.

Ingestion: If swallowed, do NOT induce vomiting. Wash mouth with water and contact a Poisons Information Centre, or call a doctor.

Section 5 - Fire Fighting Measures

Fire and Explosion Hazards: This product is classified as a C2 combustible product. There is no risk of an explosion from this product under normal circumstances if it is involved in a fire. Violent steam generation or eruption may occur upon application of direct water stream on hot liquids.

Fire decomposition products from this product may be toxic if inhaled. Take appropriate protective measures.

Extinguishing Media: Preferred extinguishing media are carbon dioxide, dry chemical, foam, water fog. Water fog or fine spray is the preferred medium for large fires. Ensure that no spillage enters drains or water courses.

Fire Fighting: If a significant quantity of this product is involved in a fire, call the fire brigade.

Flash point: Approx 235°C

Upper Flammability Limit: No data.

Lower Flammability Limit: No data.

Autoignition temperature: No data.

Flammability Class: C2

Section 6 - Accidental Release Measures

Accidental release: In the event of a major spill, prevent spillage from entering drains or water courses. Wear full protective clothing including eye/face protection. All skin areas should be covered. See below under Personal Protection regarding Australian Standards relating to personal protective equipment. Suitable materials for protective clothing include rubber, PVC. Eye/face protective equipment should comprise as a minimum, protective glasses and, preferably, goggles. If there is a significant chance that vapours or mists are likely to build up in the cleanup area, we recommend that you use a respirator. It should be fitted with a type A cartridge, suitable for organic vapours.

Stop leak if safe to do so, and contain spill. Absorb onto sand, vermiculite or other suitable absorbent material. If spill is too large or if absorbent material is not available, try to create a dike to stop material spreading or going into drains or waterways. Because of the environmentally hazardous nature of this product, special care should be taken to restrict release to waterways or drains. Sweep up and shovel or collect recoverable product into labelled containers



Material Safety Data Sheet

for recycling or salvage, and dispose of promptly. Recycle containers wherever possible after careful cleaning. After spills, wash area preventing runoff from entering drains. If a significant quantity of material enters drains, advise emergency services. This material may be suitable for approved landfill. Ensure legality of disposal by consulting regulations prior to disposal. Thoroughly launder protective clothing before storage or re-use. Advise laundry of nature of contamination when sending contaminated clothing to laundry.

Section 7 - Handling and Storage

Handling: Keep exposure to this product to a minimum, and minimise the quantities kept in work areas. Check Section 8 of this MSDS for details of personal protective measures, and make sure that those measures are followed. The measures detailed below under "Storage" should be followed during handling in order to minimise risks to persons using the product in the workplace. Also, avoid contact or contamination of product with incompatible materials listed in Section 10.

Storage: This product is a Scheduled Poison. Observe all relevant regulations regarding sale, transport and storage of this schedule of poison. Check packaging - there may be further storage instructions on the label.

Section 8 - Exposure Controls and Personal Protection

The following Australian Standards will provide general advice regarding safety clothing and equipment:

Respiratory equipment: **AS/NZS 1715**, Protective Gloves: **AS 2161**, Industrial Clothing: **AS2919**, Industrial Eye Protection: **AS1336** and **AS/NZS 1337**, Occupational Protective Footwear: **AS/NZS2210**.

Exposure Limits	TWA (mg/m ³)	STEL (mg/m ³)
Dibutyl tin dilaurate	0.1	0.2

No special equipment is usually needed when occasionally handling small quantities. The following instructions are for bulk handling or where regular exposure in an occupational setting occurs without proper containment systems.

Ventilation: No special ventilation requirements are normally necessary for this product. However make sure that the work environment remains clean and that vapours and mists are minimised.

Eye Protection: Protective glasses or goggles should be worn when this product is being used. Failure to protect your eyes may cause them harm. Emergency eye wash facilities are also recommended in an area close to where this product is being used.

Skin Protection: Prevent skin contact by wearing impervious gloves, clothes and, preferably, apron. Make sure that all skin areas are covered. See below for suitable material types.

Protective Material Types: We suggest that protective clothing be made from the following materials: 4H, Butyl, Neoprene, Nitrile or PVC Coated.

Respirator: Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned above.

Eyebaths or eyewash stations and safety deluge showers should be provided near to where this product is being used.

Section 9 - Physical and Chemical Properties:

Physical Description & colour:	Yellowish liquid.
Odour:	Mild odour.
Boiling Point:	204°C at 100kPa
Freezing/Melting Point:	Approximately 17°C.
Volatiles:	No specific data. Expected to be low at 100°C.
Vapour Pressure:	Negligible at normal ambient temperatures.
Vapour Density:	No data.
Specific Gravity:	1.05
Water Solubility:	<0.1g/L at 20°C.
pH:	No data.
Volatility:	No data.
Odour Threshold:	No data.
Evaporation Rate:	No data.
Coeff Oil/water distribution:	No data
Autoignition temp:	No data.



Material Safety Data Sheet

Section 10 - Stability and Reactivity

Reactivity: This product is unlikely to react or decompose under normal storage conditions. However, if you have any doubts, contact the supplier for advice on shelf life properties.

Conditions to Avoid: This product should be kept in a cool place, preferably below 30°C. Keep containers tightly closed. Keep containers and surrounding areas well ventilated.

Incompatibilities: strong oxidising agents, strong acids, strong bases.

Fire Decomposition: Carbon dioxide, and if combustion is incomplete, carbon monoxide and smoke. Water, tin compounds. Carbon monoxide poisoning produces headache, weakness, nausea, dizziness, confusion, dimness of vision, disturbance of judgment, and unconsciousness followed by coma and death.

Polymerisation: This product will not undergo polymerisation reactions.

Section 11 - Toxicological Information

Local Effects:

Target Organs: no data

Classification of Hazardous Ingredients

Dibutyl Tin Dilaurate: LD₅₀ Oral, Rat 2070mg/kg LD₅₀ Dermal, Rabbit = >2000mg/kg

Section 12 - Ecological Information

Very toxic to aquatic organisms, may cause long-term adverse effects to the aquatic environment. Insufficient data to be sure of biodegradability status. Treat as not biodegradable.

Fish: LC₅₀ Orange-red killifish: 1mg/L (48hr) LC₅₀ golden orfe: 2mg/L

Daphnia: EC₅₀ 0.66mg/L

Section 13 - Disposal Considerations

Disposal: Containers should be emptied as completely as practical before disposal. If possible, recycle containers either in-house or send to recycle company. If this is not practical, send to a commercial waste disposal site. This product should be suitable for incineration. Please do NOT dispose into sewers or waterways.

Section 14 - Transport Information

ADG Code: 3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

Hazchem Code: 2X

Special Provisions: SP179, SP274

Dangerous Goods Class: Class 9, Miscellaneous Dangerous Goods.

Packaging Group: III

Packaging Method: 3.8.9

Class 9 Miscellaneous Dangerous Goods shall not be loaded in the same vehicle or packed in the same freight container with Classes 1 (Explosives), 5.1 (Oxidising Agents where the Miscellaneous Dangerous Goods are Fire Risk Substances), 5.2 (Organic Peroxides where the Miscellaneous Dangerous Goods are Fire Risk Substances). They may however be loaded in the same vehicle or packed in the same freight container with Classes 2.1 (Flammable Gases), 2.2 (Non-Flammable, Non-Toxic Gases), 2.3 (Toxic Gases), 3 (Flammable liquids), 4.1 (Flammable Solids), 4.2 (Spontaneously Combustible Substances), 4.3 (Dangerous When Wet Substances), 5.1 (Oxidising Agents except where the Miscellaneous Dangerous Goods are Fire Risk Substances), 5.2 (Organic Peroxides except where the Miscellaneous Dangerous Goods are Fire Risk Substances), 6 (Toxic Substances), 7 (Radioactive Substances), 8 (Corrosive Substances), Foodstuffs and foodstuff empties.

Section 15 - Regulatory Information

AICS: This product was found in the public AICS Database.

The following ingredient: Dibutyl tin dilaurate (tin organic compounds), is mentioned in the SUSDP.

Section 16 - Other Information

This MSDS contains only safety-related information. For other data see product literature.

Acronyms:

Issued by: GE Silicones Australia Pty Ltd
Product: RTV 577

Page 4 of 5

Phone 1800 034 427 (Business Hours)
This version issued: November, 2006



GE Silicones

Material Safety Data Sheet

ADG Code	Australian Code for the Transport of Dangerous Goods by Road and Rail
AICS	Australian Inventory of Chemical Substances
CAS number	Chemical Abstracts Service Registry Number
Hazchem Code	Emergency action code of numbers and letters that provide information to emergency services especially firefighters
IARC	International Agency for Research on Cancer
NOHSC	National Occupational Health and Safety Commission
NOS	Not otherwise specified
NTP	National Toxicology Program (USA)
R-Phrase	Risk Phrase
SUSDP	Standard for the Uniform Scheduling of Drugs & Poisons
UN Number	United Nations Number

THIS MSDS SUMMARISES OUR BEST KNOWLEDGE OF THE HEALTH AND SAFETY HAZARD INFORMATION OF THE PRODUCT AND HOW TO SAFELY HANDLE AND USE THE PRODUCT IN THE WORKPLACE. EACH USER MUST REVIEW THIS MSDS IN THE CONTEXT OF HOW THE PRODUCT WILL BE HANDLED AND USED IN THE WORKPLACE.

IF CLARIFICATION OR FURTHER INFORMATION IS NEEDED TO ENSURE THAT AN APPROPRIATE RISK ASSESSMENT CAN BE MADE, THE USER SHOULD CONTACT THIS COMPANY SO WE CAN ATTEMPT TO OBTAIN ADDITIONAL INFORMATION FROM OUR SUPPLIERS. OUR RESPONSIBILITY FOR PRODUCTS SOLD IS SUBJECT TO OUR STANDARD TERMS AND CONDITIONS, A COPY OF WHICH IS SENT TO OUR CUSTOMERS AND IS ALSO AVAILABLE ON REQUEST.

Please read all labels carefully before using product.

This MSDS was prepared by Kilford & Kilford Pty Ltd in accord with the NOHSC document "National Code of Practice for the Preparation of Material Safety Data Sheets" 2nd Edition [NOHSC:2011(2003)]

<http://www.kilford.com.au/> Phone (02)9251 4532

End of MSDS