

GAP-SEAL

GE91A

ACRYLIC GAP SEALANT

DESCRIPTION

GE91A Gap-Seal is a flexible, one component acrylic latex caulk for interior and exterior gaps and joints.

KEY PERFORMANCE PROPERTIES

- **Paintable**
- **Water Based**
- **One Part**
- **Flexible**

APPLICATIONS

GE91A Gap-Seal displays excellent adhesion to concrete, masonry, wood, brick, glass, ceramic tiles and plasterboard.

GE91A Gap-Seal is ideal for sealing interior and exterior wall joints not subjected to significant joint movement or pooling of water.

APPLICATIONS

All surfaces must be clean, dry and free of dust, oil, grease or any other contamination. Cut nozzle at a 45 degree angle, slightly wider than the required bead. Apply sealant by gunning into joint, ensuring complete contact with sides and avoid air voids. Tool with spatula within 5 minutes and clean off excess with water before the sealant cures.

Do not apply below 5C or when rain is expected.

SPECIFICATIONS

Typical product data should not be used as specifications. Product specification sheets are available upon request from GE Plastics (Aust) Pty Ltd.

TYPICAL PRODUCT DATA

PROPERTY	VALUE
Colour	White
Specific Gravity	1.65 g/ml
Solids	85 %
Application Temperature	5-40 C
Shore A hardness	40
100% Modulus	0.7 MPa
Elongation at Break	200 %
Skin Time - 20C/55%RH	5 minutes
Joint Movement Capability	+/- 7.5 %

GAP-SEAL

GE91A

ACRYLIC GAP SEALANT

PACKAGING

GE91A is available in 20 x 450gm cartridges.

Shelf life is 12 months if stored between 5C and 25C. Do not allow to freeze.
Packed in Australia

HEALTH AND

Contact with uncured product will irritate eyes. In case of eye contact immediately flush with water for 15 minutes and seek medical advice. Avoid contact with skin.
Use in well-ventilated areas and avoid breathing vapours. Keep out of reach of children.

LIMITATION

GE91A is not recommended for underwater applications and external applications where the temperature exceeds 80C.

Available From